



OVERLAP SHRINK MACHINE (without sealing bar)

FAST 600 TRAY

Stainless steel frame



POLYPACK SECS
DISSAY-SOUS-COURCILLON
72500 CHÂTEAU DU LOIR France
TEL. : +33 (0)2 43 44 03 94 - FAX. : +33 (0)2 43 79 49 74
www.polypack.fr - [E.mail : polypack@polypack.fr](mailto:polypack@polypack.fr)

FAST 600 TRAY



Principle

- Shrink wrapping by overlapping without sealing mark, subsequently sealed and shrunk in a tunnel
- Film type : plain or printed polyethylene film
- Width of film : 600 mm
- In line in feed products
- Film cutting by programmed length or spot reading
- Overlapping
- Shrinking and auto sealing under the bundle
- Change over quick and easy
- Manual film reel connection by sealing bar
- Film reel on rack support \varnothing 400 or 500 m
- Capacity : up to 60 cycles/mn

Technical specifications

- Stainless steel construction
- Safety panels with large windows, total access to all parts
- Film cutting by rotative film
- Positive up feed film by belt conveyor without vacuum chamber.
- Shrink tunnel :
 - Stainless steel mesh conveyor mounted on hollow stem driven by motorized link on each side
 - Inner ventilation by turbines
 - Tangential cooling by turbines
- PLC control in electric cabinet integrated on the side
- Main voltage: 400 volts triphasis
- Control voltage : 24 volts
- Power supply : 25 at 45 KVA
- Operating air pressure : 6 bars
- Centralized lubrication on common rail; automatic in option
- Safety and control indicators
- Equipment built meets EC-norms compliances
- Equipment delivered with maintenance and operation manual.

