



WRAP AROUND TRAY / CASE PACKER

PACK V/WA

Stainless steel frame



POLYPACK SECS

DISSAY-SOUS-COURCILLON
72500 CHÂTEAU DU LOIR France
TEL. : +33 (0)2 43 44 03 94 - FAX. : +33 (0)2 43 79 49 74
www.polypack.fr - [E.mail : polypack@polypack.fr](mailto:polypack@polypack.fr)

PACK V/WA



Principle

- V/WA : Filling a tray/case erected from a blank and wrap around closed in continuous motion
- Blank cardboard magazine on the side with lateral in feed to the grouping or lower blank magazine with high capacity for front in feed product
- Tray forming with small / high sides, upper horizontal flaps
- Lateral/In line in feed product
- Grouping pattern selecting adapted
- Straight/90° transfer by (open) horizontal flight bars conveyor
- Change over quick and easy
- Capacity : up to 50 cycles/mn

Technical specifications

- Stainless steel construction
- Safety panels with large windows, total access to all parts
- Venturi vacuum sucker device for blank extraction
- Folding blank during the motion through upper & lower wrap
- Setting at right angles in the ramps
- Hot melt gluing device
- PLC control in electric cabinet integrated in the frame or outside
- Main voltage: 400 volts triphasis
- Control voltage : 24 volts
- Power supply : 10 -15 KVA
- Operating air pressure : 6 bars
- Centralized lubrication on common rail; automatic in option
- Safety and control indicators
- Equipment built meets EC-norms compliances
- Equipment delivered with maintenance and operating manual

Options

- Divider device for square shape
- Multi pattern with quick and easy change over by wheel and screw
- 90° out feed
- Hot melt gluing device different from POLYPACK standard

