



MULTIPACK Valisette Machine

PACK VALISETTE

Stainless steel frame



POLYPACK SECS

DISSAY-SOUS-COURCILLON

72500 CHÂTEAU DU LOIR France

TEL. : +33 (0)2 43 44 03 94 - FAX. : +33 (0)2 43 79 49 74

www.polypack.fr - [E.mail : polypack@polypack.fr](mailto:polypack@polypack.fr)

PACK VALISETTE

Technical specifications

- Stainless steel construction.
- Safety panels with large windows, total access to all parts.
- Hot melt gluing device.
- Centralized lubrication on common rail; automatic in option.
- PLC control in electric cabinet on the side or above.
- Safety and control indicators.
- Main voltage: 400 volts triphasis (other on request)
- Control voltage : 24 volts.
- Power supply : 10 KVA
- Operating air pressure : 6 bars.
- Equipment built meets EC-norms compliances.
- Equipment delivered with maintenance and operation manual.

Principle

- Filling a case opened on the sides, erected from a blank and wrap around closed in continuous motion.
- Front in feed products on the blank cardboard.
- Lower blank magazine with high capacity (up to 750 blanks).
- Different types of cardboard allowed : micro, small, medium, big flute corrugated carton or Kraft carton.
- Change over quick and easy by wheel and screw.
- Capacity: up to 50 cycles/min.

