



AUTOMATIC SHRINK WRAPPING MACHINE (with sealing bar)

POLY U

Stainless steel frame



Packaging machines

DISSAY-SOUS-COURCILLON

72500 CHÂTEAU DU LOIR France

TEL : +33 (0)2 43 44 03 94 - FAX : +33 (0)2 43 79 49 74

www.polypack.fr - E.mail : polypack@polypack.fr

Poly U



Principle

- Collecting and handling products in a film wrapped around bundle by pushing in a film curtain which is subsequently cut and sealed by a sealing bar and shrunk in a tunnel
- Film : plain polyethylene film
- Width of film : 600 - 800 - 1000 - 1200 (other on request)
- Upper sealing bar stroke length : adapted to the products
- Rate: in accordance with products and bulking (up to 30sets per min.)
- SF Step by step machine with welding when stopping.
- SA continuing machine with accompanying welding.
- Manually feeding machine, very flexible.
- Especially adapted machine to packing up for unsteady products and disparate bulkings.
- Machine originally developed for copacker.

Technical specifications

- Stainless steel construction
- Continual heating sealing bar mounted on a fixed station and contrary moving electrode on bottom..
- Shrink tunnel with warm air recycling
- Power in accordance with rate and products: 10- 15- 20- 30 KVA
- Main voltage : 400 volts triphasis.
- Control voltage : 24 volts.
- Operating air pressure : 6 bars.
- Ventilation and cooling in exit.
- Programmable PLC.
- Equipment built meets EC-norms compliances
- Equipment delivered with maintenance and operation manual

Options :

- Multi pattern



Packaging machines