


# Semi-Automatic SHRINK WRAPPING MACHINE (with sealing bar)

# POLY S

**Stainless steel frame**



**POLYPACK SECS**  
DISSAY-SOUS-COURCILLON  
72500 CHÂTEAU DU LOIR France  
TEL. : +33 (0)2 43 44 03 94 - FAX. : +33 (0)2 43 79 49 74  
www.polypack.fr - [E.mail : polypack@polypack.fr](mailto:polypack@polypack.fr)

## Poly S



### Principle

- Collecting and handling products in a film wrapped around bundle by pushing in a film curtain which is subsequently cut and sealed by a sealing bar and shrunk in a tunnel
- Film : plain polyethylene film
- Width of film : 600 - 800 - 1000 - 1200 (other on request)
- Upper sealing bar stroke length: adapted to the products
- Capacity: up to 12 cycles/mn
- **S**  
Manual in feed products semi-automatically loading in the film curtain.

### Technical Specifications

- Stainless steel construction.
- Continual heating sealing bar mounted on a fixed station.
- Shrink tunnel:
  - Stainless steel mesh conveyor mounted on hollow stem driven by motorized links on each side.
  - Inner ventilation by turbines.
  - Cooling fan by turbines
- Control without PLC
- Main voltage: 400 volts Triphasis.
- Control voltage: 24 volts
- Power supply: 10-15-20-30 KVA.
- Operating Air Pressure : 6 bars.
- Safety and control indicators.
- Equipment built meets EC-Norms compliances.
- Equipment delivered with maintenance and operation manual.

